



Datasheet Spectro pad[®] Series 2

Technical data

- Measuring modes:
 - Reflectance spot color with Delta E
 - Reflectance strip scanning with automatic patch detection (linearization, profiling),
 - DOC (Digital Output Control – optional) with pass/ fail analysis
- Measurement: manual with expandable ruler for X-direction and roller guide for Y-direction
- Positioning: with laser pointer
- Measuring aperture: 6 mm diameter
- Patch size: 12x12 mm recommended
- Scanning speed: max. 200 meas./sec
- Maximum strip length: 290 mm
- Geometry: 45:0
- Physical illumination:
 - 3 point circumferential,
 - 7 LED-chip D50 illumination
- ISO 13655-2009 measuring mode M1 and additional M0, M2 (UVcut)
- Measuring sensor:
 - diffraction grating with diode array
- Spectral range: 380 ... 750 nm
- Spectral resolution: 2 nm
- Optical resolution: 10 nm
- Calibration:
 - manual with internal white reference
- Short term repeatability:
 - < 0,2 ΔE_{00} on white
- Inter-instrument agreement:
 - 0,5 ΔE_{00} average, 1,0 ΔE_{00} max.,
 - on BCRA Series II tiles
- Internal memory: 2 GByte Ports: USB 1.1, WiFi 2,4 GHz IEEE 802.11b+g
 - Open, WEP, WPA, WPA2 Security
 - FCC (USA), IC (Canada), CE (Europe), MIC (Japan), KCC (South Korea) Certified



- Display: 320x240 pixel, touch screen
- Battery: Li-Ion accumulator (2 hours continuous measurement)
- Interface:
 - USB and WiFi for Mac, PC and Linux
- Temperature sensor:
 - range -20 ... +50 °C (-4 ... +122 °F)
 - resolution 0,1 accuracy: +/- 1,0
- Humidity sensor:
 - range 0 ... 100 %
 - resolution 1 accuracy: +/- 5%
- Dimensions: 210 x 220 x 90 mm (LxWxH)
- Weight: 1,4 kg

System requirements

- Microsoft Windows XP or later (32 and 64 bit)
- Mac OS X 10.5 or later (Intel)
- Including free measuring software Barbieri Gateway for Mac and PC

Accessories:

- 110...240 Volt charger with international adapters
- USB cable
- Cleaning tissue